

NOTICE OF REVISION (NOR)		1. DATE (YYMMDD) 96-04-05		Form Approved OMB No. 0704-0188	
THIS REVISION DESCRIBED BELOW HAS BEEN AUTHORIZED FOR THE DOCUMENT LISTED.					
<small>Public reporting burden for this collection is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. PLEASE DO NOT RETURN YOUR COMPLETED FORM TO EITHER OF THESE ADDRESSES. RETURN COMPLETED FORM TO THE GOVERNMENT ISSUING CONTRACTING OFFICER FOR THE CONTRACT/ PROCURING ACTIVITY NUMBER LISTED IN ITEM 2 OF THIS FORM.</small>				2. PROCURING ACTIVITY NO.	
				3. DODAAC	
4. ORIGINATOR		b. ADDRESS (Street, City, State, Zip Code) Defense Electronics Supply Center 1507 Wilmington Pike Dayton, OH 45444-5765		5. CAGE CODE 67268	
a. TYPED NAME (First, Middle Initial, Last)				7. CAGE CODE 67268	
6. NOR NO. 5962-R091-96		8. DOCUMENT NO. 5962-95520			
9. TITLE OF DOCUMENT MICROCIRCUIT, MEMORY, DIGITAL, CMOS, FIELD PROGRAMMABLE GATE ARRAY, 2500 GATES, MONOLITHIC SILICON			10. REVISION LETTER		11. ECP NO. N/A
			a. CURRENT b. NEW A		
12. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES All					
13. DESCRIPTION OF REVISION Sheet 1: Revisions ltr column; add "A". Revisions description column; add "Changes in accordance with NOR 5962-R091-96". Revisions date column; add "96-04-05". Rev status above sheet numbers 1 and 6, add "A". Revision level block; Add "A". Sheet 6: Table 1, parameter; "Binning circuit delay", change limit for device 01 from 125 ns to 82.3 ns, and change device 02 from 106 ns to 70 ns. Revision level block; add "A".					
14. THIS SECTION FOR GOVERNMENT USE ONLY					
a. (X one)		<input checked="checked" type="checkbox"/> (1) Existing document supplemented by the NOR may be used in manufacture. <input type="checkbox"/> (2) Revised document must be received before manufacturer may incorporate this change. <input type="checkbox"/> (3) Custodian of master document shall make above revision and furnish revised document.			
b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT DESC-ELDS			c. TYPED NAME (First, Middle Initial, Last) Michael A. Frye		
d. TITLE Microelectronics Branch Chief		e. SIGNATURE Michael A. Frye		f. DATE SIGNED (YYMMDD) 96-04-05	
15a. ACTIVITY ACCOMPLISHING REVISION DESC-ELDS		b. REVISION COMPLETED (Signature) Kenneth S. Rice		c. DATE SIGNED (YYMMDD) 96-04-05	

REVISIONS																			
LTR	DESCRIPTION										DATE (YR-MO-DA)					APPROVED			
REV																			
SHEET																			
REV																			
SHEET	15	16	17																
REV STATUS OF SHEETS				REV															
				SHEET		1	2	3	4	5	6	7	8	9	10	11	12	13	14
PMIC N/A				PREPARED BY KENNETH RICE						DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444									
STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A				CHECKED BY JEFF BOWLING															
				APPROVED BY MICHAEL FRYE															
				DRAWING APPROVAL DATE 95-08-08															
								REVISION LEVEL						SIZE A		CAGE CODE 67268		5962-95520	
										SHEET 1 OF 17									

DESC FORM 193

JUL 94


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

5962-E154-95

1. SCOPE

1.1 Scope. This drawing forms a part of a one part - one part number documentation system (see 6.6 herein). Two product assurance classes consisting of military high reliability (device classes Q and M) and space application (device class V), and a choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). Device class M microcircuits represent non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices". When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

1.2 PIN. The PIN shall be as shown in the following example:



1.2.1 Radiation hardness assurance (RHA) designator. Device class M RHA marked devices shall meet the MIL-I-38535 appendix A specified RHA levels and shall be marked with the appropriate RHA designator. Device classes Q and V RHA marked devices shall meet the MIL-I-38535 specified RHA levels and shall be marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) shall identify the circuit function as follows:

Device type	Generic number	Circuit function	Bin Speed
01	1425A	2500 gate, field programmable gate array	82.3 ns
02	1425A-1	2500 gate, field programmable gate array	70 ns

1.2.3 Device class designator. The device class designator shall be a single letter identifying the product assurance level as follows:

Device class	Device requirements documentation
M	Vendor self-certification to the requirements for non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883
Q or V	Certification and qualification to MIL-I-38535

1.2.4 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
X	CMGA5 - PN	133	Pin grid array
Y	See figure 1	132	Flat pack

1.2.5 Lead finish. The lead finish shall be as specified in MIL-STD-883 (see 3.1 herein) for class M or MIL-I-38535 for classes Q and V. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 2

1.3 Absolute maximum ratings. 1/

DC supply voltage range (V_{DD})	-0.5 V dc to +7.0 V dc
Input voltage range (V_i)	-0.5 V dc to $V_{DD} + 0.5$ V dc
Output voltage range (V_o)	-0.5 V dc to $V_{DD} + 0.5$ V dc
I/O Source/Sink current (I_{IO})	± 20 mA
Storage temperature range (T_{STG})	-65°C to +150°C
Lead temperature (soldering, 10 seconds)	300°C
Thermal resistance, junction-to-case (θ_{JC}) :	
Case X	See MIL-STD-1835
Case Y	11°C/W 2/
Maximum junction temperature (T_J)	+175°C

1.4 Recommended operating conditions.

Supply voltage (V_{DD})	+4.5 V dc to +5.5 V dc
Case operating temperature range (T_C)	-55°C to +125°C

1.5 Digital logic testing for device classes Q and V.

Fault coverage measurement of manufacturing
logic tests (MIL-STD-883, test method 5012)- XX percent 3/

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, bulletin, and handbook. Unless otherwise specified, the following specification, standards, bulletin, and handbook of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MICROCIRCUIT

MIL-I-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

MICROCIRCUIT

MIL-STD-883 - Test Methods and Procedures for Microelectronics.
MIL-STD-973 - Configuration Management.
MIL-STD-1835 - Microcircuit Case Outlines.

BULLETIN

MICROCIRCUIT

MIL-BUL-103 - List of Standard Microcircuit Drawings (SMD's).

HANDBOOK

MICROCIRCUIT

MIL-HDBK-780 - Standardized Military Drawings.

(Copies of the specification, standards, bulletin, and handbook required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

- 1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
- 2/ When the thermal resistance for this case is specified in MIL-STD-1835, that value shall supersede the value indicated herein.
- 3/ When a QML source exists, a value shall be provided.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 3

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ELECTRONICS INDUSTRIES ASSOCIATION (EIA)

JEDEC Standard No. 17 - A Standard Test Procedure for the Characterization
LATCH-UP in CMOS Integrated Circuits.

(Applications for copies should be addressed to the Electronics Industries Association, 2500 Wilson Boulevard, Arlington, VA 22201.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM Standard F1192-88 - Standard Guide for the Measurement of Single Event Procedures from
Heavy Ion Irradiation of Semiconductor Devices.

(Applications for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device class M shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein. The individual item requirements for device classes Q and V shall be in accordance with MIL-I-38535, the device manufacturer's Quality Management (QM) plan, and as specified herein. The modification in the QM plan shall not effect the form, fit, or function as described herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-STD-883 (see 3.1 herein) for device class M and MIL-I-38535 for device classes Q and V and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein and figure 1.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 2.

3.2.3 Truth table.

3.2.3.1 Unprogrammed devices. The truth table or test vectors for unprogrammed devices for contracts involving no altered item drawing is not part of this drawing. When required in screening (see 4.2 herein) or quality conformance inspection group A, B, C, D, or E (see 4.4 herein), the devices shall be programmed by the manufacturer prior to test. A minimum of 50 percent of the total number of logic modules shall be utilized or at least 25 percent of the total logic modules shall be utilized for any altered item drawing pattern.

3.2.3.2 Programmed devices. The truth table or test vectors for programmed devices shall be as specified by an attached altered item drawing.

3.2.4 Radiation exposure circuit. The radiation exposure circuit will be provided when RHA product becomes available.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. Marking for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein). In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103. Marking for device classes Q and V shall be in accordance with MIL-I-38535.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 4

3.5.1 Certification/compliance mark. The compliance mark for device class M shall be a "C" as required in MIL-STD-883 (see 3.1 herein). The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-I-38535.

3.6 Certificate of compliance. For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.8.2 herein). For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.8.1 herein). The certificate of compliance submitted to DESC-EC prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device class M, the requirements of MIL-STD-883 (see 3.1 herein), or for device classes Q and V, the requirements of MIL-I-38535 and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required for device class M in MIL-STD-883 (see 3.1 herein) or for device classes Q and V in MIL-I-38535 shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DESC-EC of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-STD-973.

3.9 Verification and review for device class M. For device class M, DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 42 (see MIL-I-38535, appendix A).

3.11 Processing options. Since the device is capable of being programmed by either the manufacturer or the user to result in a wide variety of configurations, two processing options are provided for selection in the contract.

3.11.1 Unprogrammed device delivered to the user. All testing shall be verified through group A testing as defined in 3.2.3.1 and table IIA. It is recommended that users perform subgroups 7 and 9 after programming to verify the specific program configuration.

3.11.2 Manufacturer-programmed device delivered to the user. All testing requirements and quality assurance provisions herein, including the requirements of the altered item drawing, shall be satisfied by the manufacturer prior to delivery.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device class M, sampling and inspection procedures shall be in accordance with MIL-STD-883 (see 3.1 herein). For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-I-38535 and the device manufacturer's QM plan. The modification in the QM plan shall not effect the form, fit, or function as described herein.

4.2 Screening. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. For device classes Q and V, screening shall be in accordance with MIL-I-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes M.

a. Delete the sequence specified as initial (pre-burn-in) electrical parameters through interim (post-burn-in) electrical parameters of method 5004 and substitute lines 1 through 6 of table IIA herein.

b. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. For device class M the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.

(1) Dynamic burn-in for device classes M (method 1015 of MIL-STD-883, test condition D; for circuit, see 4.2.1b herein).

c. Interim and final electrical parameters shall be as specified in table IIA herein.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 5

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{DD} ≤ 5.5 V ^{1/} unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output low voltage	V _{OL}	test one output at a time, V _{DD} = 4.5 V, I _{OL} = 6.0 mA	1,2,3	ALL		0.4	V
Output high voltage	V _{OH}	test one output at a time, V _{DD} = 4.5 V, I _{OH} = -4.0 mA	1,2,3	ALL	3.7		V
Input low voltage	V _{IL}		1,2,3	ALL		0.8	V
Input high voltage	V _{IH}		1,2,3	ALL	2.0		V
Standby supply current	I _{DD}	outputs unloaded, V _{DD} = 5.5 V, V _{IN} = V _{DD} or GND	1,2,3	ALL		25	mA
Input leakage current	I _{IL}	V _{DD} = 5.5 V, V _{IN} = V _{DD} or GND	1,2,3	ALL	-10	10	μA
Output leakage current	I _{OZ}	V _{DD} = 5.5 V, V _{IN} = V _{DD} or GND	1,2,3	ALL	-10	10	μA
I/O terminal capacitance	C _{I/O}	See 4.4.1c, f = 1.0 MHz, V _{OUT} = 0 V	4	ALL		20	pF
Functional tests	FT ^{2/}	See 4.4.1e	7,8A,8B	ALL			
Binning circuit delay	t _{PBLH}	See figure 3, V _{IL} = 0 V, V _{IH} = 3.0 V, V _{DD} = 4.5 V, V _{OUT} = 1.5 V ^{3/}	9,10,11	01		125	ns
	t _{PBHL}			02		106	

^{1/} All tests shall be performed under the worst case condition unless otherwise specified.

^{2/} Devices are functionally tested using a serial scan test method. Data is shifted into the SDI pin and the DCLK pin is used as a clock. The data is used to drive the inputs of the internal logic and I/O modules, allowing a complete functional test to be performed. The outputs of the module can be read by shifting out the output response or by monitoring the PRA, PRB or SDO pins. These tests form a part of the manufacturer's test tape and shall be maintained and available at the approved source(s) of supply upon request by DESC or the OEM.

^{3/} Binning circuit delay is defined as the input-to-output delay of a special path called the "binning circuit". The binning circuit consists of one input buffer plus 16 combinatorial logic modules plus one output buffer. The logic modules are distributed along the left side of the device. These modules are configured as non-inverting buffers and are connected through programmed antifuses with typical capacitive loading.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


5962-95520

REVISION LEVEL

SHEET

6

Case Y



132 Pin Flat pack - top view

Clarification: The tie bar on this page is for reference, see following page for tie bar details.

FIGURE 1. Case outline.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


5962-95520

REVISION LEVEL

SHEET

7

Case Y



Bottom view

Clarification: The package is for reference, see previous page for package detail.

FIGURE 1. Case outline - Continued.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-95520

REVISION LEVEL

SHEET

8

Case Y




FIGURE 1. Case outline - Continued.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-95520

REVISION LEVEL

SHEET

9

Case Y

CASE Y				
SYMBOL	METRIC		INCHES	
	MIN	MAX	MIN	MAX
A	2.18	3.56	.086	0.14
A1	1.98	3.18	.078	.125
A2	0.15	0.30	.006	.012
b	0.18	0.33	.007	.013
b1	0.18	0.25	.007	.010
c	0.10	0.20	.004	.009
c1	0.10	0.15	.004	.006
D1/E1	23.75	24.51	0.935	0.965
D2/E2	20.32 BSC		.800 BSC	
D3/E3	10.16 BSC		.400 BSC	
e	0.64 BSC		.025 BSC	
F	8.26	9.53	.325	.375
J	0.76	1.02	.030	.040
K	---	0.51	---	.020
L	63.50	64.52	2.500	2.540
L1	63.12	63.63	2.485	2.505
L2	37.59	38.61	1.480	1.520
M	---	0.04	---	.0015

NOTES:

1. A terminal 1 identification mark shall be located at the index corner in the shaded area shown. Terminal 1 is located immediately adjacent to and counterclockwise from the index corner. Terminal numbers increase in a counterclockwise direction when viewed as shown.
2. Vendor option.
3. Generic lead attach dogleg depiction. May be flat lead configuration. Includes lead attach dogleg height and lid height, whichever is greater. Dimension A and A1 do not include heat sinks or other attached features.
4. Although dimensions are in inches, the US government preferred system of measurement is the metric SI system. However, this item was originally designed using inch-pound units of measurement, in the event of conflict between the two, the inch-pound units shall take precedence.
5. All exposed metalized areas and leads are gold plated 100 microinches (2.5 μ m) minimum thickness over 80 to 350 microinches (2.0 to 8.9 μ m) thickness of nickel.
6. Tolerances unless otherwise specified: $\pm 1\%$ N.L.T. ± 0.005 .
7. N = number of terminals

FIGURE 1. Case outline - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 10

Case outline X

Device type	All		Device type	All		Device type	All		All	Device type
Terminal number	Terminal symbol		Terminal number	Terminal symbol		Terminal number	Terminal symbol		Terminal number	Terminal symbol
A1	NC		D1	I/O		H13	I/O		M11	SDD, I/O
A2	GNDQ		D2	I/O		J1	I/O		M12	VCC
A3	I/O		D3	I/O		J2	VSV		M13	I/O
A4	I/O		D4	DCLK, I/O		J3	I/O		N1	NC
A5	I/O		D6	I/O		J11	I/O		N2	I/O
A6	PRBA, I/O		D7	CLKA, I/O		J12	VSV		N3	I/O
A7	NC		D8	I/O		J13	I/O		N4	I/O
A8	I/O		D11	I/O		K1	I/O		N5	I/O
A9	I/O		D12	I/O		K2	I/O		N6	I/O
A10	I/O		D13	I/O		K3	BININ, I/O		N7	NC
A11	I/O		E1	I/O		K6	I/O		N8	I/O
A12	I/O		E2	I/O		K7	FCLK, I/O		N9	I/O
A13	NC		E3	MODE		K8	I/O		N10	I/O
B1	I/O		E11	VPP		K11	I/O		N11	I/O
B2	VCC		E12	I/O		K12	I/O		N12	GNDQ
B3	I/O		E13	I/O		K13	I/O		N13	NC
B4	I/O		F1	I/O		L1	I/O			
B5	I/O		F2	I/O		L2	I/O			
B6	CLKB, I/O		F3	I/O		L3	GND			
B7	VCC		F4	I/O		L4	BINOUT, I/O			
B8	I/O		F10	VKS		L5	I/O			
B9	I/O		F11	I/O		L6	PRBB, I/O			
B10	I/O		F12	I/O		L7	GND			
B11	I/O		F13	I/O		L8	I/O			
B12	VCC		G1	NC		L9	I/O			
B13	I/O		G2	VCC		L10	IOPCL, I/O			
C1	I/O		G3	GND		L11	GND			
C2	SDI, I/O		G4	I/O		L12	I/O			
C3	GND		G10	I/O		L13	I/O			
C4	I/O		G11	GND		M1	I/O			
C5	I/O		G12	VCC		M2	VCC			
C6	I/O		G13	NC		M3	GNDQ			
C7	GND		H1	I/O		M4	I/O			
C8	I/O		H2	I/O		M5	I/O			
C9	I/O		H3	I/O		M6	I/O			
C10	IOCLK, I/O		H4	I/O		M7	VCC			
C11	GND		H10	I/O		M8	I/O			
C12	GNDQ		H11	I/O		M9	I/O			
C13	I/O		H12	I/O		M10	I/O			

NC = NO CONNECT

FIGURE 2. Terminal Connections.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-95520

REVISION LEVEL

SHEET

11

Case outline Y

Device type	All	Device type	All	Device type	All
Terminal number	Terminal symbol	Terminal number	Terminal symbol	Terminal number	Terminal symbol
1	NC	54	I/O	107	VCC
2	GNDQ	55	I/O	108	I/O
3	SDI, I/O	56	I/O	109	I/O
4	I/O	57	I/O	110	I/O
5	I/O	58	GND	111	I/O
6	I/O	59	VCC	112	I/O
7	I/O	60	I/O	113	I/O
8	I/O	61	I/O	114	I/O
9	MODE	62	I/O	115	I/O
10	VCC	63	SDO, I/O	116	CLKA, I/O
11	GND	64	IOPCL, I/O	117	CLKB, I/O
12	I/O	65	GNDQ	118	PRBA, I/O
13	I/O	66	NC	119	I/O
14	I/O	67	NC	120	I/O
15	I/O	68	I/O	121	I/O
16	I/O	69	I/O	122	GND
17	I/O	70	I/O	123	VCC
18	I/O	71	I/O	124	I/O
19	I/O	72	I/O	125	I/O
20	I/O	73	I/O	126	I/O
21	I/O	74	GND	127	I/O
22	VSV	75	VCC	128	I/O
23	I/O	76	I/O	129	I/O
24	I/O	77	I/O	130	I/O
25	I/O	78	VSV	131	DCLK, I/O
26	GND	79	I/O	132	NC
27	VCC	80	I/O		
28	I/O	81	I/O		
29	I/O	82	I/O		
30	I/O	83	I/O		
31	I/O	84	I/O		
32	I/O	85	I/O		
33	BININ, I/O	86	I/O		
34	NC	87	I/O		
35	INOUT, I/O	88	I/O		
36	GNDQ	89	VPP		
37	I/O	90	GND		
38	I/O	91	VCC		
39	I/O	92	VKS		
40	I/O	93	I/O		
41	I/O	94	I/O		
42	GND	95	I/O		
43	VCC	96	I/O		
44	I/O	97	I/O		
45	I/O	98	IOCLK, I/O		
46	I/O	99	NC		
47	I/O	100	NC		
48	PRBB, I/O	101	GNDQ		
49	I/O	102	I/O		
50	FCLK, I/O	103	I/O		
51	I/O	104	I/O		
52	I/O	105	I/O		
53	I/O	106	GND		

NC = NO CONNECT

FIGURE 2. Terminal connections - Continued.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-95520

REVISION LEVEL

SHEET

12




FIGURE 3. Switching test circuit and waveforms.

STANDARD
 MICROCIRCUIT DRAWING
 DEFENSE ELECTRONICS SUPPLY CENTER
 DAYTON, OHIO 45444

SIZE
 A

5962-95520

REVISION LEVEL

SHEET

13

4.2.2 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition, and test temperature or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in appendix B of MIL-I-38535.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-I-38535. Inspections to be performed shall be those specified in MIL-I-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Quality conformance inspection for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein) and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4). Technology conformance inspection for classes Q and V shall be in accordance with MIL-I-38535 including groups A, B, C, D, and E inspections and as specified herein except where option 2 of MIL-I-38535 permits alternate in-line control testing.

4.4.1 Group A inspection.

- a. Tests shall be as specified in table IIA herein.
- b. Subgroups 5 and 6 of table I of method 5005 of MIL-STD-883 shall be omitted.
- c. Subgroup 4 ($C_{1/0}$ measurements) shall be measured only for the initial test and after any process or design changes which may affect input or output capacitance. A sample size of five devices with no failures, on a minimum of 10 worst case pins from each device.
- d. O/V (latch-up) tests shall be measured only for initial qualification and after any design or process changes which may affect the performance of the device. For device class M procedures and circuits shall be maintained under document revision level control by the manufacturer and shall be made available to the preparing activity or acquiring activity upon request. For device classes Q and V, the procedures and circuits shall be under the control of the device manufacturer's (TRB) in accordance with MIL-I-38535 and shall be made available to the preparing activity or acquiring activity upon request. Testing shall be on all pins, on 5 devices with zero failures. Latch-up test shall be considered destructive. Information contained in JEDEC standard number 17 may be used for reference.
- e. Programmed device (see 3.2.3.2) - For device class M, subgroups 7, 8A, and 8B tests shall consist of verifying the functionality of the device. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device. These tests shall have been fault graded in accordance with MIL-STD-883, test method 5012 (see 1.5 herein).
- f. Unprogrammed devices shall be tested for programmability and dc and ac performance compliance to the requirements of group A, subgroups 1 and 7.
 - (1) A sample shall be selected from each wafer lot to satisfy programmability requirements. Eight devices shall be submitted to programming (see 3.2.3.1). If any device fails to program, the lot shall be rejected. At the manufacturer's option, the sample may be increased to 13 total devices with no more than one total device failure allowable.
 - (2) These eight devices shall also be submitted to the requirements of the specified tests of group A, subgroups 1 and 7. If any device fails, the lot shall be rejected. At the manufacturer's option, the sample may be increased to 13 total devices with no more than one total device failure allowable.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 14

(3a) Eight devices from the programmability sample shall be submitted to the requirements of group A, subgroups 9 for binning circuit delay only. If any device fails, the lot shall be rejected. At the manufacturer's option, the sample may be increased to 13 total devices with no more than one total device failure allowable.

(3b) If the binning circuit is tested on 100 percent of the products, then the above requirement is met.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein. Delta limits shall apply only to subgroup 1 of group C inspection and shall consist of tests specified in table IIB herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

a. Test condition D. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005.

b. $T_A = +125^{\circ}\text{C}$, minimum.

c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition, and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein). RHA levels for device classes Q and V shall be M, D, L, R, F, G, and H and for device class M shall be M and D.

a. End-point electrical parameters shall be as specified in table IIA herein.

b. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-I-38535, appendix A, for the RHA level being tested. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-I-38535 for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^{\circ}\text{C} \pm 5^{\circ}\text{C}$, after exposure, to the subgroups specified in table IIA herein.

c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

4.5 Delta measurements for device class V. Delta measurements, as specified in table IIA, shall be made and recorded before and after the required burn-in screens and steady-state life tests to determine delta compliance. The electrical parameters to be measured, with associated delta limits are listed in table IIB. The device manufacturer may at his option, either perform delta measurements or within 24 hours after life test perform final electrical parameter tests, subgroups 1, 7, and 9.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-STD-883 (see 3.1 herein) for device class M and MIL-I-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 15

TABLE IIA. Electrical test requirements. 1/ 2/ 3/ 4/ 5/ 6/ 7/

Line no.	Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-I-38535, table III)	
		Device class M	Device class Q	Device class V
1	Interim electrical parameters (see 4.2)			1,7,9
2	Static burn-in (method 1015)	Not Required	Not Required	Not Required
3	Same as line 1			1*,7* Δ
4	Dynamic burn-in (method 1015)	Required	Required	Required
5	Final electrical parameters	1*,2,3,7*, 8A,8B,9,10, 11	1*,2,3,7*, 8A,8B,9,10, 11	1*,2,3,7*, 8A,8B,9, 10,11
6	Group A test requirements	1,2,3,4**,7, 8A,8B,9,10, 11	1,2,3,4**,7, 8A,8B,9,10, 11	1,2,3,4**,7, 8A,8B,9,10, 11
7	Group C end-point electrical parameters	2,3,7, 8A,8B	2,3,7, 8A,8B	1,2,3,7, 8A,8B,9, 10,11 Δ
8	Group D end-point electrical parameters	2,3, 8A,8B	2,3, 8A,8B	2,3, 8A,8B
9	Group E end-point electrical parameters	1,7,9	1,7,9	1,7,9

1/ Blank spaces indicate tests are not applicable.

2/ Any or all subgroups may be combined when using high-speed testers.

3/ Subgroups 7 and 8 functional tests shall verify the truth table.

4/ * indicates PDA applies to subgroup 1 and 7.

5/ ** see 4.4.1e.

6/ Δ indicates delta limit (see table IIB) shall be required where specified, and the delta values shall be computed with reference to the previous interim electrical parameters (see line 1).

7/ See 4.4.1d

STANDARD
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-95520

REVISION LEVEL

SHEET

16

TABLE IIB. Delta limits at +25°C.

Test 1/	Device types
	All
I_{DD}	± 1.0 mA
I_{OZ}	± 2.0 μ A
t_{PBLH} , t_{PBHL}	± 10 ns

1/ The above parameters shall be recorded before and after the required burn-in and life test to determine the delta.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-973 using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and which SMD's are applicable to that system. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DESC-EC, telephone (513) 296-6047.

6.4 Comments. Comments on this drawing should be directed to DESC-EC, Dayton, Ohio 45444-5270, or telephone (513) 296-5377.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-I-38535 and MIL-STD-1331.

6.6 One part - one part number system. The one part - one part number system described below has been developed to allow for transitions between identical generic devices covered by the three major microcircuit requirements documents (MIL-H-38534, MIL-I-38535, and 1.2.1 of MIL-STD-883) without the necessity for the generation of unique PIN's. The three military requirements documents represent different class levels, and previously when a device manufacturer upgraded military product from one class level to another, the benefits of the upgraded product were unavailable to the Original Equipment Manufacturer (OEM), that was contractually locked into the original unique PIN. By establishing a one part number system covering all three documents, the OEM can acquire to the highest class level available for a given generic device to meet system needs without modifying the original contract parts selection criteria.

Military documentation format	Example PIN under new system	Manufacturing source listing	Document listing
New MIL-H-38534 Standard Microcircuit Drawings	5962-XXXXXZZ(H or K)YY	QML-38534	MIL-BUL-103
New MIL-I-38535 Standard Microcircuit Drawings	5962-XXXXXZZ(Q or V)YY	QML-38535	MIL-BUL-103
New 1.2.1 of MIL-STD-883 Standard Microcircuit Drawings	5962-XXXXXZZ(M)YY	MIL-BUL-103	MIL-BUL-103

6.7 Sources of supply.

6.7.2 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DESC-EC and have agreed to this drawing.

6.7.3 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-ECC.

STANDARD MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-95520
		REVISION LEVEL	SHEET 17

STANDARD MICROCIRCUIT DRAWING SOURCE APPROVAL BULLETIN

DATE: 95-08-08

Approved sources of supply for SMD 5962-95520 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-EC. This bulletin is superseded by the next dated revision of MIL-BUL-103.

Standardized military drawing PIN	Vendor CAGE number	Vendor similar PIN <u>1/</u>
5962-9552001MXX	0J4Z0	A1425A PG133B
5962-9552001MYX	0J4Z0	A1425A CQ132B
5962-9552002MXX	0J4Z0	A1425A-1 PG133B
5962-9552002MYX	0J4Z0	A1425A-1 CQ132B

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

0J4Z0

Vendor name
and address

Actel Corporation
955 East Arques Ave.
Sunnyvale, CA 94086

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.